

nerūsaļošā tērauds

stainless steel

T-pieces
trejgabali
тройники

ASTM-A 403
DIN 2605

| outs.diam. ārējais diam. наружный diam. | x | wall thckn sienīgas biež. толщина стенки mm | INCH-GAS-SCH dimensions izmērs размер | Weight svars вєс Theor. kg/pce | radius rādiuss радиус | type tips тип | tp 304/304L 1.4301/1.4306 | | tp 316/316L 1.4401/1.4404 | |
|---|---|--|--|--|-----------------------------|---------------------|------------------------------|----|------------------------------|----|
| | | | | | | | W | S | W | S |
| 10.20 | x | 2.00 | | 0.01 | 15.0 | 3S | | | | x |
| 12.00 | x | 2.00 | | 0.02 | 15.0 | 3S | | | | x |
| 13.50 | x | 1.60 | | 0.02 | 20.5 | 1.5d | | | x | |
| 13.50 | x | 2.30 | | 0.02 | 17.5 | 3S | | | | x |
| 15.00 | x | 2.00 | | 0.02 | 20.0 | 3S | | | | x |
| 17.20 | x | 1.60 | | 0.02 | 28.5 | 1.5d | | | x | |
| 17.20 | x | 1.60 | | 0.03 | 30.0 | 5d | x | | x | |
| 17.20 | x | 2.30 | | 0.03 | 22.5 | 3S | | | | x |
| 18.00 | x | 1.50 | | 0.02 | 22.5 | 3S | | | x | |
| 20.00 | x | 1.50 | | 0.03 | 24.0 | 3S | x | | x | |
| 20.00 | x | 1.50 | | 0.03 | 30.0 | 1.5d | x | | x | |
| 20.00 | x | 2.00 | | 0.03 | 24.0 | 3S | x | | x | |
| 20.00 | x | 2.00 | | 0.03 | 30.0 | 1.5d | x | | x | |
| 21.30 | x | 1.60 | | 0.03 | 38.1 | 1.5d | x | | x | |
| 21.30 | x | 2.00 | | 0.04 | 26.0 | 3S | x | | x | |
| 21.30 | x | 2.00 | | 0.04 | 38.1 | 1.5d | x | | x | |
| 21.30 | x | 2.00 | | 0.06 | 45.0 | 5d | x | | x | |
| 21.30 | x | 2.60 | | 0.06 | 26.0 | 3S | x | | x | |
| 21.30 | x | 2.60 | | 0.06 | 38.1 | 1.5d | x | | x | |
| 21.34 | x | 1.65 | 1/2" SCH 5S | 0.03 | 38.1 | LR | x | | x | |
| 21.34 | x | 2.11 | 1/2" SCH 10S | 0.11 | 38.1 | LR | x | x | x | x |
| 21.34 | x | 2.77 | 1/2" SCH 40S | 0.14 | 38.1 | LR | x | x | x | x |
| 21.34 | x | 3.73 | 1/2" SCH 80S | 0.18 | 38.1 | LR | | x | | x |
| 21.34 | x | 4.78 | 1/2" SCH 160S | 0.23 | 38.1 | LR | | xe | | xe |
| 23.00 | x | 1.50 | | 0.04 | 34.5 | 1.5d | xe | | xe | |
| 23.00 | x | 1.50 | | 0.08 | 60.0 | 3d | xe | | xe | |
| 25.00 | x | 1.50 | | 0.04 | 38.0 | 1.5d | x | | x | |
| 25.00 | x | 2.00 | | 0.05 | 38.0 | 1.5d | x | | x | |
| 26.67 | x | 1.65 | 3/4" SCH 5S | 0.06 | 38.1 | LR | x | | x | |
| 26.67 | x | 2.11 | 3/4" SCH 10S | 0.07 | 38.1 | LR | x | x | x | x |
| 26.67 | x | 2.87 | 3/4" SCH 40S | 0.08 | 38.1 | LR | x | x | x | x |
| 26.67 | x | 3.91 | 3/4" SCH 80S | 0.10 | 38.1 | LR | | x | | x |
| 26.67 | x | 5.56 | 3/4" SCH 160S | 0.14 | 38.1 | LR | | xe | | xe |
| 26.90 | x | 1.60 | | 0.05 | 28.5 | 1.5d | x | | x | |
| 26.90 | x | 2.00 | | 0.06 | 28.5 | 1.5d | x | | x | |
| 26.90 | x | 2.00 | | 0.18 | 57.5 | 5d | x | | x | |
| 26.90 | x | 2.60 | | 0.08 | 28.5 | 1.5d | x | | x | |
| 28.00 | x | 1.50 | | 0.06 | 42.0 | 1.5d | x | | x | |
| 28.00 | x | 1.50 | | 0.12 | 75.0 | 3d | xe | | xe | |
| 28.00 | x | 2.00 | | 0.07 | 42.0 | 1.5d | x | | x | |
| 30.00 | x | 1.50 | | 0.05 | 45.0 | 1.5d | x | | x | |
| 30.00 | x | 2.00 | | 0.07 | 45.0 | 1.5d | x | | x | |
| 32.00 | x | 1.50 | | 0.05 | 48.0 | 1.5d | x | | x | |
| 32.00 | x | 2.00 | | 0.07 | 48.0 | 1.5d | x | | x | |
| 33.00 | x | 1.50 | | 0.14 | 49.5 | 1.5d | x | | x | |
| 33.00 | x | 1.50 | | 0.28 | 90.0 | 3d | xe | | xe | |

neržaviejoji tērauds

stainless steel

elbows 90°
cauruļu līkumi 90°
отводы

ASTM-A 403
DIN 2605

| outs.diam. ārējais diam. наружный диам. | wall thckn sienīgas biez. толщина стенки | INCH-GAS-SCH dimensions izmērs размер | Weight svars вес Theor. kg/pce | radius rādiuss радиус | type tips тип | tp 304/304L 1.4301/1.4306 | | tp 316/316L 1.4401/1.4404 | | |
|---|--|--|--|-----------------------------|---------------------|------------------------------|----|------------------------------|----|----|
| | | | | | | W | S | W | S | |
| | | | | | | x | mm | | | |
| 33.40 | x | 1.65 | 1" SCH 5S | 0.07 | 38.1 | LR | x | | x | |
| 33.40 | x | 2.77 | 1" SCH 10S | 0.11 | 25.4 | SR | xe | xe | xe | xe |
| 33.40 | x | 2.77 | 1" SCH 10S | 0.14 | 38.1 | LR | x | x | x | x |
| 33.40 | x | 3.38 | 1" SCH 40S | 0.13 | 25.4 | SR | xe | xe | xe | xe |
| 33.40 | x | 3.38 | 1" SCH 40S | 0.15 | 38.1 | LR | x | x | x | x |
| 33.40 | x | 4.55 | 1" SCH 80S | 0.19 | 38.1 | LR | | x | | x |
| 33.40 | x | 5.56 | 1" SCH 160 | 0.23 | 38.1 | LR | | xe | | xe |
| 33.70 | x | 1.60 | | 0.08 | 38.0 | 1.5d | x | | x | |
| 33.70 | x | 2.00 | | 0.10 | 38.0 | 1.5d | x | | x | |
| 33.70 | x | 2.00 | | 0.20 | 72.5 | 5d | x | | x | |
| 33.70 | x | 2.60 | | 0.12 | 38.0 | 1.5d | x | | x | |
| 33.70 | x | 3.20 | | 0.14 | 38.0 | 1.5d | x | | x | |
| 35.00 | x | 1.50 | | 0.10 | 52.5 | 1.5d | x | | | |
| 38.00 | x | 1.50 | | 0.11 | 57.0 | 1.5d | x | | x | |
| 38.00 | x | 2.00 | | 0.13 | 57.0 | 1.5d | x | | x | |
| 40.00 | x | 1.50 | | 0.11 | 60.0 | 1.5d | x | | x | |
| 40.00 | x | 2.00 | | 0.16 | 60.0 | 1.5d | x | | x | |
| 42.16 | x | 1.65 | 1.1/4" SCH 5S | 0.12 | 47.6 | LR | x | | x | |
| 42.16 | x | 2.77 | 1.1/4" SCH 10S | 0.16 | 31.8 | SR | xe | xe | xe | xe |
| 42.16 | x | 2.77 | 1.1/4" SCH 10S | 0.23 | 47.6 | LR | x | x | x | x |
| 42.16 | x | 3.56 | 1.1/4" SCH 40S | 0.21 | 31.8 | SR | xe | xe | xe | xe |
| 42.16 | x | 3.56 | 1.1/4" SCH 40S | 0.26 | 47.6 | LR | x | x | x | x |
| 42.16 | x | 4.85 | 1.1/4" SCH 80S | 0.35 | 47.6 | LR | | x | | x |
| 42.16 | x | 6.35 | 1.1/4" SCH 160 | 0.46 | 47.6 | LR | | xe | | xe |
| 42.40 | x | 1.60 | | 0.14 | 47.6 | 1.5d | x | | x | |
| 42.40 | x | 2.00 | | 0.15 | 47.6 | 1.5d | x | | x | |
| 42.40 | x | 2.00 | | 0.30 | 92.5 | 5d | x | | x | |
| 42.40 | x | 2.60 | | 0.19 | 47.6 | 1.5d | x | | x | |
| 42.40 | x | 3.20 | | 0.23 | 47.6 | 1.5d | x | | x | |
| 43.00 | x | 1.50 | | 0.15 | 47.5 | 3s | x | | x | |
| 43.00 | x | 1.50 | | 0.30 | 120.0 | 3d | xe | | xe | |
| 44.00 | x | 2.00 | | 0.46 | 140.0 | d + 100 | x | | x | |
| 44.50 | x | 2.00 | | 0.17 | 66.0 | 1.5d | x | | x | |
| 48.26 | x | 1.65 | 1.1/2" SCH 5S | 0.17 | 57.2 | LR | x | | x | |
| 48.26 | x | 2.77 | 1.1/2" SCH 10S | 0.22 | 38.1 | SR | xe | xe | xe | xe |
| 48.26 | x | 2.77 | 1.1/2" SCH 10S | 0.30 | 57.2 | LR | x | x | x | x |
| 48.26 | x | 3.68 | 1.1/2" SCH 40S | 0.28 | 38.1 | SR | xe | xe | xe | xe |
| 48.26 | x | 3.68 | 1.1/2" SCH 40S | 0.40 | 57.2 | LR | x | x | x | x |
| 48.26 | x | 5.08 | 1.1/2" SCH 80S | 0.49 | 57.2 | LR | | x | | x |
| 48.26 | x | 7.14 | 1.1/2" SCH 160 | 0.65 | 57.2 | LR | | xe | | xe |
| 48.30 | x | 1.60 | | 0.19 | 57.1 | 1.5d | x | | x | |
| 48.30 | x | 2.00 | | 0.22 | 57.1 | 1.5d | x | | x | |
| 48.30 | x | 2.00 | | 0.44 | 109.5 | 5d | x | | x | |
| 48.30 | x | 2.60 | | 0.26 | 57.1 | 1.5d | x | | x | |
| 48.30 | x | 3.20 | | 0.32 | 57.1 | 1.5d | x | | x | |
| 50.00 | x | 1.50 | | 0.22 | 75.0 | 1.5d | x | | x | |

neržavējošā tēraus

stainless steel

elbows 90°
cauruļu līkumi 90°
отводы

ASTM-A 403
DIN 2605

| outs.diam. ārējais diam. наружный диам. | x | wall thckn sienīgas biez. толщина стенки mm | INCH-GAS-SCH dimensions izmērs размер | Weight svars вес Theor. kg/pc | radius rādiuss радиус | type tips тип | tp 304/304L 1.4301/1.4306 | | tp 316/316L 1.4401/1.4404 | |
|---|---|--|--|---|-----------------------------|---------------------|------------------------------|----|------------------------------|----|
| | | | | | | | W | S | W | S |
| | | | | | | | | | | |
| 50.00 | x | 2.00 | | 0.31 | 75.0 | 1.5d | x | | x | |
| 50.80 | x | 1.50 | | 0.22 | 75.0 | 1.5d | x | | x | |
| 50.80 | x | 2.00 | | 0.31 | 75.0 | 1.5d | x | | x | |
| 50.80 | x | 2.50 | | 0.35 | 75.0 | 1.5d | | | x | |
| 53.00 | x | 1.50 | | 0.26 | 79.5 | 1.5d | x | | | |
| 53.00 | x | 1.50 | | 0.52 | 150.0 | 3d | xe | | xe | |
| 54.00 | x | 2.00 | | 0.30 | 75.0 | 1.5d | x | | x | |
| 54.00 | x | 2.00 | | 0.62 | 150.0 | d+100 | x | | x | |
| 57.00 | x | 2.00 | | 0.34 | 72.0 | 3S | x | | | |
| 57.00 | x | 3.00 | | 0.48 | 72.0 | 3S | x | | | |
| 60.30 | x | 1.60 | | 0.29 | 76.2 | 1.5d | x | | x | |
| 60.30 | x | 2.00 | | 0.34 | 76.2 | 1.5d | x | | x | |
| 60.30 | x | 2.00 | | 0.68 | 137.5 | 5d | x | | x | |
| 60.30 | x | 2.60 | | 0.44 | 76.2 | 1.5d | x | | x | |
| 60.30 | x | 3.60 | | 0.62 | 76.2 | 1.5d | x | | x | |
| 60.33 | x | 1.65 | 2" SCH 5S | 0.28 | 76.2 | LR | x | | x | |
| 60.33 | x | 2.77 | 2" SCH 10S | 0.48 | 50.8 | SR | xe | xe | xe | xe |
| 60.33 | x | 2.77 | 2" SCH 10S | 0.50 | 76.2 | LR | x | x | x | x |
| 60.33 | x | 3.91 | 2" SCH 40S | 0.36 | 50.8 | SR | xe | xe | xe | xe |
| 60.33 | x | 3.91 | 2" SCH 40S | 0.70 | 76.2 | LR | x | x | x | x |
| 60.33 | x | 5.54 | 2" SCH 80S | 0.89 | 76.2 | LR | | x | | x |
| 60.33 | x | 8.74 | 2" SCH 160 | 1.33 | 76.2 | LR | | xe | | xe |
| 63.50 | x | 1.50 | | 0.34 | 82.5 | 3S | | | x | |
| 63.50 | x | 1.50 | | 0.34 | 94.5 | 1.5d | x | | | |
| 64.00 | x | 2.00 | | 0.42 | 90.0 | 1.5d | | xe | | xe |
| 69.00 | x | 2.00 | | 0.87 | 165.0 | d + 100 | x | | x | |
| 70.00 | x | 2.00 | | 0.50 | 92.0 | i.5d | x | | x | |
| 70.00 | x | 3.00 | | 0.72 | 92.0 | 1.5d | x | | x | |
| 73.03 | x | 2.11 | 2.1/2" SCH 5S | 0.54 | 95.0 | LR | x | | x | |
| 73.03 | x | 3.05 | 2.1/2" SCH 10S | 0.52 | 63.5 | SR | xe | xe | xe | xe |
| 73.03 | x | 3.05 | 2.1/2" SCH 10S | 0.79 | 95.0 | LR | x | x | x | x |
| 73.03 | x | 5.16 | 2.1/2" SCH 40S | 0.92 | 63.5 | SR | xe | xe | xe | xe |
| 73.03 | x | 5.16 | 2.1/2" SCH 40S | 1.29 | 95.0 | LR | x | x | x | x |
| 73.03 | x | 7.01 | 2.1/2" SCH 80S | 1.70 | 95.0 | LR | | xe | xe | |
| 76.10 | x | 1.50 | | 0.50 | 96.0 | 1.5d | x | | x | |
| 76.10 | x | 2.00 | | 0.62 | 96.0 | 1.5d | x | | x | |
| 76.10 | x | 2.00 | | 0.87 | 175.0 | 5d | x | | x | |
| 76.10 | x | 3.00 | | 0.88 | 96.0 | 1.5d | x | | x | |
| 76.10 | x | 3.60 | | 1.08 | 96.0 | 1.5d | x | | x | |
| 84.00 | x | 2.00 | | 0.77 | 120.0 | 1.5d | x | | x | |
| 84.00 | x | 2.00 | | 1.17 | 180.0 | d + 100 | x | | x | |
| 88.90 | x | 2.00 | | 0.79 | 114.5 | 1.5d | x | | x | |
| 88.90 | x | 2.00 | | 1.42 | 207.5 | 5d | x | | x | |
| 88.90 | x | 3.00 | | 1.17 | 114.5 | 1.5d | x | | x | |
| 88.90 | x | 4.00 | | 1.65 | 114.5 | 1.5d | x | | x | |

neržaviojūšā stāl

neržaviojūšais tērauds

stainless steel

elbows 90°
sauruļu lūkumi 90°
отводы

ASTM-A 403
DIN 2605

| outs.diam. ārējais diam. mm | x | wall thckn sienīgas biez. толщина стенки mm | INCH-GAS-SCH dimensions izmērs размер | Weight svars вєс Theor. kg/pce | radius rādiuss радиус | type tips тип | tp 304/304L 1.4301/1.4306 | | tp 316/316L 1.4401/1.4404 | |
|-----------------------------------|---|--|--|--|-----------------------------|---------------------|------------------------------|----|------------------------------|----|
| | | | | | | | W | S | W | S |
| 88.90 | x | 2.11 | 3" SCH 5S | 0.81 | 114.3 | LR | x | | x | |
| 88.90 | x | 3.05 | 3" SCH 10S | 0.84 | 76.1 | SR | xe | xe | xe | xe |
| 88.90 | x | 3.05 | 3" SCH 10S | 1.18 | 114.3 | LR | x | x | x | x |
| 88.90 | x | 5.49 | 3" SCH 40S | 1.49 | 76.1 | SR | xe | xe | xe | xe |
| 88.90 | x | 5.49 | 3" SCH 40S | 2.14 | 114.3 | LR | x | x | x | x |
| 88.90 | x | 7.62 | 3" SCH 80S | 2.74 | 114.3 | LR | | xe | | xe |
| 88.90 | x | 7.14 | 3" SCH 160 | 3.83 | 114.3 | LR | | xe | | xe |
| 101.60 | x | 1.50 | | 0.95 | 133.5 | 1.5d | x | | x | |
| 101.60 | x | 2.00 | | 1.20 | 133.5 | 1.5d | x | | x | |
| 101.60 | x | 3.00 | | 1.50 | 133.5 | 1.5d | x | | x | |
| 104.00 | x | 2.00 | | 1.20 | 150.0 | 1.5d | x | | x | |
| 104.00 | x | 2.00 | | 1.61 | 200.0 | d+100 | x | | x | |
| 108.00 | x | 2.00 | | 1.10 | 142.5 | 1.5d | x | | x | |
| 108.00 | x | 3.00 | | 1.85 | 142.5 | 1.5d | x | | x | |
| 108.00 | x | 4.00 | | 2.20 | 142.5 | 3S | x | | x | |
| 114.30 | x | 2.00 | | 1.35 | 152.5 | 1.5d | x | | x | |
| 114.30 | x | 2.00 | | 2.39 | 270.0 | 5d | x | | x | |
| 114.30 | x | 3.00 | | 2.01 | 152.5 | 1.5d | x | | x | |
| 114.30 | x | 4.00 | | 2.67 | 152.5 | 1.5d | x | | x | |
| 114.30 | x | 2.11 | 4" SCH 5S | 1.41 | 152.4 | LR | x | | x | |
| 114.30 | x | 3.05 | 4" SCH 10S | 1.38 | 101.6 | SR | xe | xe | xe | xe |
| 114.30 | x | 3.05 | 4" SCH 10S | 2.03 | 152.4 | LR | x | x | x | x |
| 114.30 | x | 6.02 | 4" SCH 40S | 2.65 | 101.6 | SR | xe | xe | xe | xe |
| 114.30 | x | 6.02 | 4" SCH 40S | 4.03 | 152.4 | LR | x | x | x | x |
| 114.30 | x | 8.56 | 4" SCH 80S | 5.34 | 152.4 | LR | | xe | | xe |
| 114.30 | x | 13.49 | 4" SCH 160 | 8.02 | 152.4 | LR | | xe | | xe |
| 129.00 | x | 2.00 | | 1.86 | 187.0 | 1.5d | x | | x | |
| 129.00 | x | 2.00 | | 2.26 | 225.0 | d+100 | x | | x | |
| 139.70 | x | 2.00 | | 2.07 | 190.5 | 1.5d | x | | x | |
| 139.70 | x | 3.00 | | 3.08 | 190.5 | 1.5d | x | | x | |
| 139.70 | x | 4.00 | | 4.10 | 190.5 | 1.5d | x | | x | |
| 141.30 | x | 2.77 | 5" SCH 5S | 2.95 | 190.5 | LR | xe | | xe | |
| 141.30 | x | 3.40 | 5" SCH 10S | 2.37 | 127.0 | SR | xe | | xe | |
| 141.30 | x | 3.40 | 5" SCH 10S | 3.46 | 190.5 | LR | xe | xe | xe | xe |
| 141.30 | x | 6.55 | 5" SCH 40S | 4.32 | 127.0 | SR | xe | xe | xe | xe |
| 141.30 | x | 6.55 | 5" SCH 40S | 6.51 | 190.5 | LR | xe | xe | xe | xe |
| 141.30 | x | 9.53 | 5" SCH 80S | 9.25 | 190.5 | LR | | xe | | xe |
| 154.00 | x | 2.00 | | 2.69 | 225.0 | 1.5d | x | | x | |
| 154.00 | x | 2.00 | | 3.00 | 250.0 | d + 100 | x | | x | |
| 156.00 | x | 3.00 | | 4.06 | 225.0 | 1.5d | x | | x | |
| 168.28 | x | 2.77 | 6" SCH 5S | 4.12 | 228.6 | LR | x | | x | |
| 168.28 | x | 3.40 | 6" SCH 10S | 3.36 | 152.4 | SR | xe | xe | xe | xe |
| 168.28 | x | 3.40 | 6" SCH 10S | 5.03 | 228.6 | LR | x | xe | x | xe |
| 168.28 | x | 7.11 | 6" SCH 40S | 6.87 | 152.4 | SR | xe | xe | xe | xe |
| 168.28 | x | 7.11 | 6" SCH 40S | 10.90 | 228.6 | LR | x | xe | x | xe |
| 168.28 | x | 10.97 | 6" SCH 80S | 15.30 | 228.6 | LR | | xe | | xe |
| 168.30 | x | 2.00 | | 3.00 | 228.5 | 1.5d | x | | x | |

neržaviejoji tērauds

stainless steel

elbows 90°
sauruju līkumi 90°
отводы

ASTM-A 403
DIN 2605

| outs.diam. ārējais diam. наружный диам. | x | wall thckn sienīgas biez. толщина стенки mm | INCH-GAS-SCH dimensions izmērs размер | Weight svars вес Theor. kg/pce | radius rādiuss радиус | type tips тип | tp 304/304L 1.4301/1.4306 | | tp 316/316L 1.4401/1.4404 | |
|---|---|--|--|--|-----------------------------|---------------------|------------------------------|----|------------------------------|----|
| | | | | | | | W | S | W | S |
| 168.30 | x | 3.00 | | 4.56 | 228.5 | 1.5d | x | | x | |
| 168.30 | x | 4.00 | | 6.07 | 228.5 | 1.5d | x | | x | |
| 204.00 | x | 2.00 | | 4.78 | 300.0 | d + 100 | x | | x | |
| 206.00 | x | 3.00 | | 7.21 | 300.0 | d + 100 | x | | x | |
| 219.08 | x | 2.77 | 8" SCH 5S | 7.20 | 304.8 | LR | x | | x | |
| 219.08 | x | 3.76 | 8" SCH 10S | 6.57 | 203.2 | SR | xe | | xe | |
| 219.08 | x | 3.76 | 8" SCH 10S | 9.73 | 304.8 | LR | x | | x | |
| 219.08 | x | 8.18 | 8" SCH 40S | 14.00 | 203.2 | SR | | xe | | xe |
| 219.08 | x | 8.18 | 8" SCH 40S | 21.50 | 304.8 | LR | x | xe | x | xe |
| 219.08 | x | 12.70 | 8" SCH 80S | 30.90 | 304.8 | LR | | xe | | xe |
| 219.10 | x | 2.00 | | 5.23 | 305.0 | 1.5d | x | | x | |
| 219.10 | x | 3.00 | | 7.80 | 305.0 | 1.5d | x | | x | |
| 219.10 | x | 4.00 | | 10.40 | 305.0 | 1.5d | x | | x | |
| 254.00 | x | 2.00 | | 6.97 | 350.0 | d+100 | x | | x | |
| 254.00 | x | 2.00 | | 7.42 | 375.0 | 1.5d | x | | x | |
| 256.00 | x | 3.00 | | 10.50 | 350.0 | d+100 | x | | x | |
| 273.00 | x | 2.00 | | 8.25 | 381.0 | 1.5d | x | | x | |
| 273.00 | x | 3.00 | | 12.20 | 381.0 | 1.5d | x | | x | |
| 273.00 | x | 4.00 | | 16.20 | 381.0 | 1.5d | x | | x | |
| 273.05 | x | 3.40 | 10' SCH 5S | 13.80 | 331.C | LR | x | | x | |
| 273.05 | x | 4.19 | 10' SCH 10S | 16.90 | 381.0 | LR | x | | x | |
| 273.05 | x | 9.27 | 10' SCH 40S | 38.60 | 381.0 | LR | xe | | xe | |
| 304.00 | x | 2.00 | | 10.20 | 450.0 | 1.5d | x | | x | |
| 306.00 | x | 3.00 | | 14.40 | 400.0 | d + 100 | x | | x | |
| 323.85 | x | 3.96 | 12' SCH 5S | 22.80 | 457.0 | LR | x | | x | |
| 323.85 | x | 4.57 | 12' SCH 10S | 26.30 | 457.0 | LR | x | | x | |
| 323.85 | x | 9.53 | 12' SCH 40S | 59.40 | 457.0 | LR | xe | | xe | |
| 323.90 | x | 2.00 | | 11.70 | 457.0 | 1.5d | x | | x | |
| 323.90 | x | 3.00 | | 17.40 | 457.0 | 1.5d | x | | x | |
| 355.60 | x | 3.00 | | 22.30 | 533.5 | 1.5d | x | | x | |
| 355.60 | x | 4.78 | 14' SCH 10S | 35.10 | 533.5 | LR | x | | x | |
| 355.60 | x | 9.53 | 14' SCH 40S | 70.30 | 533.5 | LR | xe | | xe | |
| 356.00 | x | 3.00 | | 18.80 | 450.0 | d + 100 | x | | x | |
| 406.00 | x | 3.00 | | 23.90 | 500.0 | d + 100 | x | | x | |
| 406.40 | x | 3.00 | | 29.10 | 602.5 | 1.5d | xe | | xe | |
| 406.40 | x | 4.78 | 16' SCH 10S | 46.00 | 609.5 | LR | x | | x | |
| 406.40 | x | 9.53 | 16' SCH 40S | 91.60 | 609.5 | LR | xe | | xe | |
| 457.20 | x | 3.00 | | 36.70 | 686.0 | 1.5d | xe | | xe | |
| 457.20 | x | 4.78 | 18' SCH 10S | 57.30 | 686.0 | LR | xe | | xe | |
| 457.20 | x | 9.53 | 18' SCH 40S | 113.00 | 686.0 | LR | xe | | xe | |
| 506.00 | x | 3.00 | | 35.70 | 600.0 | d+100 | xe | | xe | |
| 508.00 | x | 5.54 | 20' SCH 10S | 82.00 | 762.0 | LR | xe | | xe | |
| 508.00 | x | 9.52 | 20' SCH 40S | 140.00 | 762.0 | LR | xe | | xe | |
| 606.00 | x | 3.00 | | 50.00 | 700.0 | d+100 | xe | | xe | |
| 609.60 | x | 6.35 | 24' SCH 10S | 138.00 | 914.4 | LR | xe | | xe | |
| 609.60 | x | 9.52 | 24' SCH 40S | 207.80 | 914.4 | LR | xe | | xe | |